



Product Name: **Charmin Extender**

Synonyms:

Charmin Extender

Composition / Information on Ingredients

Material	%	TLV	PEL
Polypropylene	90	N/A	N/A
Galvanized Steel Spring	10	N/A	N/A

Physical and Chemical Properties

Melting Point: 160°C
Vapor Pressure: N/A
Vapor Density: N/A
Solubility in Water: Not Soluble
Ph: N/A
Specific Gravity: 0.90
% Volatile By Volume: N/A
Appearance and Odor: Granular appearance, slight to no odor.

Fire and Explosion Hazards

Flashpoint: 400°C
Auto Ignition Temperature: N/A
Flammable Limits (STP): N/A

Extinguishing Media: Use water fog, dry chemicals or CO₂

Special Fire Fighting Protective Equipment: Firefighters should be equipped with self-contained breathing apparatus

Unusual Fire and Explosion Hazards: Molten plastics, dust can cause explosion hazards.

Stability and Reactivity

Stability: Stable

Incompatibility: N/A

Hazardous Decomposition Products: CO₂, Carbon Monoxide

Hazardous Polymerization: Will not occur

Health Hazard Identification

General: Toxicity information is not available for this composite. The health hazard assessment is based on information available for the components involved in the composite.

Inhalation: Dust from product can cause irritation of the respiratory system. See precautions and personal protection (section 8 for more information) people with sensitive respiratory systems should wear respirators.

Other Effects of Overexposure: None known



Charmin Extender (cont.)

First Aid Procedures

Skin: Wash with cool water and treat for thermal burns. Do not peel off plastic from skin, but get medical treatment quickly.

Eyes: Flush with water for 15 minutes. If irritation persists, get medical attention.

Inhalation: Get to fresh air quickly.

Disposal Considerations / Spill or Leak Procedures

Disposal Method: Dispose of in Local, State or Federally approved landfill for such materials.

Spills: Sweep, vacuum or shovel into a drum for disposal or reuse. No special precautions are needed.

Exposure Controls / Personal Protection

Ventilation: Local exhaust

Respiratory: Standard MSHA / NIOSH approved respirator for dust and vapors.

Other protective equipment: Gloves, heat resistant shoes, clothing and safety glasses are recommended.

Special Precautions

None Needed

Disclaimer: The information herein is given in good faith but no warranty, expressed or implied is made.